

**Description**

Fastener Length: 1-9/16", Thread: 1/4-28, Thread Length: 27/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	BACB30LR4U18
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-591-9951



## P/N BACB30LR4U18 Specifications

<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.425 Inches Nominal
<b>Fastener Length:</b>	1.535 Inches Minimum And 1.565 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	1.115 Inches Minimum And 1.135 Inches Maximum
<b>Grip Diameter:</b>	0.249 Nominal Mils And 0.250 Nominal Centimeters
<b>Internal Drive Style:</b>	Cross Recess Type li
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Grip Length:</b>	1.115 Nominal Mils And 1.135 Nominal Centimeters
<b>Thread Quantity Per Inch:</b>	28
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Part Name Assigned By Controlling Agency:</b>	Bolt, 100 Head, Cross Recess, Long Thd, Clos Tolerance
<b>Material:</b>	Iron Alloy 660 Overall
<b>Material Document And Classification:</b>	Ams 5737 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30LR4U18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.