

Description

Fastener Length: 1-11/16", Thread: 1/4-28, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30LR4U20
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-049-7799
National Motor Freight:	013680, Alum Screws

NO IMAGE
AVAILABLE

P/N BACB30LR4U20 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.400 Inches Minimum And 0.450 Inches Maximum
Fastener Length:	1.660 Inches Minimum And 1.690 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.455 Inches Minimum And 0.510 Inches Maximum
Grip Diameter:	0.2490 Inches Minimum And 0.2495 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.250 Inches
Grip Length:	1.240 Inches Minimum And 1.260 Inches Maximum
Thread Quantity Per Inch:	28
Countersink Angle:	100.0 Degrees Nominal
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30LR4U20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.