

Description

Fastener Length: 47/64", Thread: 1/4-28, Thread Length: 31/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30LR4U4
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-112-4337
National Motor Freight:	139820, Nickel Bolts / Nails / Nuts / Rivets Etc

NO IMAGE
AVAILABLE

P/N BACB30LR4U4 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.444 Inches Minimum And 0.494 Inches Maximum
Fastener Length:	0.704 Inches Minimum And 0.734 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.446 Inches Minimum And 0.510 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Nickel Alloy K-500 Or Copper Alloy 172 Or Copper Alloy 173
Screw Material Document And Classification:	Qq-n-286 Class A Fed Spec 1st Material Response Or Qq-c-530 Fed Spec All Material Responses
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416 Type 1 Class 3 Fed Spec Single Treatment Response
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30LR4U4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.