

P/N BACB30LT3D23

Description

Fastener Length: 1-15/16", Thread: 10-32, Thread Length: 11/32"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	BACB30LT3D23
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-581-6084
Schedule B:	7318.15.8085

EAR99



ECCN:

^{*} See page 2 for technical characteristics

P/N BACB30LT3D23 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.340 Inches Minimum And 0.350 Inches Maximum
Fastener Length:	1.898 Inches Minimum And 1.948 Inches Maximum
Head Style:	Double Hexagon
Head Height:	0.130 Inches Minimum And 0.150 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Grip Diameter:	0.1879 Inches Minimum And 0.1895 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	1.428 Inches Minimum And 1.448 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	110000 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Part Name Assigned By Controlling Agency:	Bolt, 12 Point Head, Short Thread, Close Tol, A286 Cres, 110 Ksi Min Shear
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Ams Qq-p-416, Ty 2, Cl 2 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/BACB30LT3D23 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.