

P/N BACB30LT4U29

Description

Fastener Length: 1-9/16", Thread: 1/4-28, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:

Minimum Qty (MOQ):

BACB30LT4U29

1 EA

NSN: 5306-01-520-8709

Schedule B: 7318.15.8085

ECCN: EAR99



^{*} See page 2 for technical characteristics

P/N BACB30LT4U29 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.389 Inches Nominal
Fastener Length:	1.5703 Inches Nominal
Head Style:	Double Hexagon
Head Height:	0.148 Inches Nominal
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Grip Diameter:	0.2490 Inches Minimum And 0.2495 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	1.1813 Inches Nominal
Thread Quantity Per Inch:	28
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Ams5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-416, Type Ii, Class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/BACB30LT4U29 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.