



Military-Fasteners.com

P/N BACB30LT4U3

Description

Fastener Length: 37/64", Thread: 1/4-28, Thread Length: 13/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30LT4U3
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-209-9376
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N BACB30LT4U3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.364 Inches Minimum And 0.414 Inches Maximum
Fastener Length:	0.562 Inches Minimum And 0.592 Inches Maximum
Head Style:	Double Hexagon
Head Height:	0.154 Inches Minimum And 0.174 Inches Maximum
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Grip Diameter:	0.2490 Inches Minimum And 0.2495 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.179 Inches Minimum And 0.198 Inches Maximum
Thread Quantity Per Inch:	28
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Threads
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30LT4U3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.