

**Description**

Fastener Length: 1-43/64", Thread: 3/8-24, Thread Length: 31/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                                           |
|-------------------------|-------------------------------------------|
| SKU / Model:            | BACB30LT6D19                              |
| Minimum Qty (MOQ):      | 1 EA                                      |
| NSN:                    | 5306-01-211-4352                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N BACB30LT6D19 Specifications

|                                                                         |                                                                    |
|-------------------------------------------------------------------------|--------------------------------------------------------------------|
| <b>Thread Class:</b>                                                    | 3a                                                                 |
| <b>Thread Direction:</b>                                                | Right-hand                                                         |
| <b>Thread Length:</b>                                                   | 0.445 Inches Minimum And 0.495 Inches Maximum                      |
| <b>Fastener Length:</b>                                                 | 1.643 Inches Minimum And 1.673 Inches Maximum                      |
| <b>Head Style:</b>                                                      | Double Hexagon                                                     |
| <b>Head Height:</b>                                                     | 0.200 Inches Minimum And 0.220 Inches Maximum                      |
| <b>Width Between Flats:</b>                                             | 0.553 Inches Minimum And 0.564 Inches Maximum                      |
| <b>Grip Diameter:</b>                                                   | 0.3735 Inches Minimum And 0.3745 Inches Maximum                    |
| <b>Shank Unthreaded Hole Diameter:</b>                                  | 0.106 Inches Minimum And 0.116 Inches Maximum First Hole           |
| <b>Nominal Thread Diameter:</b>                                         | 0.375 Inches                                                       |
| <b>Grip Length:</b>                                                     | 1.178 Inches Minimum And 1.198 Inches Maximum                      |
| <b>Thread Quantity Per Inch:</b>                                        | 24                                                                 |
| <b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b> | 1.466 Inches Minimum And 1.528 Inches Maximum First Hole           |
| <b>Surface Finish:</b>                                                  | 32.0 Microinches Bearing Surface Of Head                           |
| <b>Surface Finish:</b>                                                  | 32.0 Microinches Threads                                           |
| <b>Special Features:</b>                                                | Green Dye Or Paint On The Thread End                               |
| <b>Material:</b>                                                        | Iron Alloy 660 Overall                                             |
| <b>Material Document And Classification:</b>                            | Ams5737 Assn Std Single Material Response Overall                  |
| <b>Surface Treatment:</b>                                               | Cadmium And Chromate Overall                                       |
| <b>Surface Treatment Document And Classification:</b>                   | Qq-p-416,type 2 Class 2 Fed Spec Single Treatment Response Overall |
| <b>Thread Series Designator:</b>                                        | Unjf                                                               |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30LT6D19> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.