

P/N BACB30LT6D19

Description

Fastener Length: 1-43/64", Thread: 3/8-24, Thread Length: 31/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: BACB30LT6D19

Minimum Qty (MOQ): 1 EA

NSN: 5306-01-211-4352

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N BACB30LT6D19 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.445 Inches Minimum And 0.495 Inches Maximum
Fastener Length:	1.643 Inches Minimum And 1.673 Inches Maximum
Head Style:	Double Hexagon
Head Height:	0.200 Inches Minimum And 0.220 Inches Maximum
Width Between Flats:	0.553 Inches Minimum And 0.564 Inches Maximum
Grip Diameter:	0.3735 Inches Minimum And 0.3745 Inches Maximum
Shank Unthreaded Hole Diameter:	0.106 Inches Minimum And 0.116 Inches Maximum First Hole
Nominal Thread Diameter:	0.375 Inches
Grip Length:	1.178 Inches Minimum And 1.198 Inches Maximum
Thread Quantity Per Inch:	24
Distance From Head Largest Bearing Surface To Shank Hole Center:	1.466 Inches Minimum And 1.528 Inches Maximum First Hole
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Threads
Special Features:	Green Dye Or Paint On The Thread End
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5737 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2 Class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/BACB30LT6D19 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.