

Description

Fastener Length: 15/32", Thread: 4-40, Thread Length: 17/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30LU043
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-231-8937
Schedule B:	8108.90.3060
ECCN:	EAR99



* See page 2 for technical characteristics

P/N BACB30LU04-3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.248 Inches Minimum And 0.278 Inches Maximum
Fastener Length:	0.424 Inches Minimum And 0.474 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.190 Inches Minimum And 0.225 Inches Maximum
Grip Diameter:	0.1105 Inches Minimum And 0.1115 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
iii End Item Identification:	Kc-46 Tanker
Nominal Thread Diameter:	0.112 Inches
Grip Length:	0.176 Inches Minimum And 0.196 Inches Maximum
Thread Quantity Per Inch:	40
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Special Features:	Faa Certified
Material:	Steel Comp 4340 Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Or Mil-s-6049 Mil Spec 2nd Material Response Or Ams 6322 Assn Std 2nd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/BACB30LU04-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.