

## P/N BACB30LU04-5

### **Description**

Fastener Length: 37/64", Thread: 4-40, Thread Length: 9/32"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: BACB30LU045

Minimum Qty (MOQ): 1 EA

NSN: 5305-01-055-1149

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# **P/N BACB30LU04-5 Specifications**

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.238 Inches Minimum And 0.288 Inches Maximum
Fastener Length:	0.560 Inches Minimum And 0.590 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.190 Inches Minimum And 0.225 Inches Maximum
Grip Diameter:	0.1105 Inches Minimum And 0.1115 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.112 Inches
Grip Length:	0.302 Inches Minimum And 0.322 Inches Maximum
Thread Quantity Per Inch:	40
Countersink Angle:	100.0 Degrees Nominal
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

## **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/close+tolerance+screws/BACB30LU04-5">https://military-fasteners.com/screws/close+tolerance+screws/BACB30LU04-5</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/screws/close+tolerance+screws/BACB30LU04-5">https://military-fasteners.com/screws/close+tolerance+screws/BACB30LU04-5</a> and selecting the quantity you