

P/N BACB30LU06-3

Description

Fastener Length: 1/2", Thread: 6-32, Thread Length: 21/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: BACB30LU063

Minimum Qty (MOQ): 15 EA

NSN: 5305-00-580-6339

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N BACB30LU06-3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.283 Inches Minimum And 0.333 Inches Maximum
Fastener Length:	0.481 Inches Minimum And 0.511 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.244 Inches Minimum And 0.279 Inches Maximum
Grip Diameter:	0.1365 Inches Minimum And 0.1375 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.138 Inches
Grip Length:	0.178 Inches Minimum And 0.198 Inches Maximum
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049rjgcams 6322 Mil Spec 2nd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unjc

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/BACB30LU06-3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.