

Description

Fastener Length: 1-7/8", Thread: 7/8-14, Thread Length: 1-1/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30LU1411X
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-435-0093
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N BACB30LU14-11X Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.184 Inches Nominal
Fastener Length:	1.8565 Inches Minimum And 1.8865 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	1.643 Inches Minimum And 1.793 Inches Maximum
Grip Diameter:	0.8886 Inches Minimum And 0.8896 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.8750 Inches
Grip Length:	0.6775 Inches Minimum And 0.6975 Inches Maximum
Thread Quantity Per Inch:	14
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416, Type 2 Class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30LU14-11X> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.