

**Description**

Fastener Length: 39/64", Thread Length: 23/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | BACB30LU24                                |
| Minimum Qty (MOQ):      | 25 EA                                     |
| NSN:                    | 5305-00-046-9975                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

# P/N BACB30LU2-4 Specifications

|                                       |  |
|---------------------------------------|--|
| Thread Class:                         | 3a   |
| Thread Length:                        | 0.320 Inches Minimum And 0.370 Inches Maximum  |
| Fastener Length:                      | 0.580 Inches Minimum And 0.610 Inches Maximum  |
| Minimum Tensile Strength:             | 160000 Pounds Per Square Inch  |
| Surface Finish:                       | 32.0 Microinches Grip  |
| Surface Finish:                       | 32.0 Microinches Threads   |
| Material:                             | Steel Comp E4340 Overall Or Steel Comp 8740 Overall  |
| Material Document And Classification: | Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049rjgcams 6322 Mil Spec 2nd Material Response Overall |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/BACB30LU2-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.