

P/N BACB30LU3-16

Military-Fasteners.com

Description

Fastener Length: 1-11/32", Thread: 10-32, Thread Length: 11/32"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	BACB30LU316
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-203-1665
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	096630, Screws Noi Brass / Bronze / Copper



P/N BACB30LU3-16 Specifications

Thread Class:	За
Thread Direction:	Right-hand
Thread Length:	0.345 Inches Nominal
Fastener Length:	1.335 Inches Minimum And 1.355 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.337 Inches Minimum And 0.383 Inches Maximum
Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.990 Inches Minimum And 1.010 Inches Maximum
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 100.0 Degrees Maximum
Material:	Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/machine+bolts/BACB30LU3-16</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.