

Description

Fastener Length: 1-51/64", Thread: 10-32, Thread Length: 23/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-------------------------------|
| SKU / Model: | BACB30LU323 |
| Minimum Qty (MOQ): | 35 EA |
| NSN: | 5305-01-055-3808 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 096640, Screws, Iron Or Steel |

NO IMAGE
AVAILABLE

P/N BACB30LU3-23 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.320 Inches Minimum And 0.370 Inches Maximum |
| Fastener Length: | 1.768 Inches Minimum And 1.798 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.337 Inches Minimum And 0.383 Inches Maximum |
| Grip Diameter: | 0.1885 Inches Minimum And 0.1895 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 1.428 Inches Minimum And 1.448 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Countersink Angle: | 100.0 Degrees Nominal |
| Surface Finish: | 32.0 Microinches Grip |
| Surface Finish: | 32.0 Microinches Threads |
| Material: | Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,type 2,type 2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30LU3-23> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.