

Description

Fastener Length: 2-11/64", Thread: 10-32, Thread Length: 23/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30LU329
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-059-1954
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N BACB30LU3-29 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.320 Inches Minimum And 0.370 Inches Maximum
Fastener Length:	2.142 Inches Minimum And 2.172 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.337 Inches Minimum And 0.383 Inches Maximum
Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Grip Length:	1.802 Inches Minimum And 1.822 Inches Maximum
Thread Quantity Per Inch:	32
Countersink Angle:	100.0 Degrees Nominal
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30LU3-29> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.