

Description

Fastener Length: 2-1/4", Thread: 1/4-28, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-------------------------------------------|
| SKU / Model: | BACB30LU429 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-01-059-1953 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N BACB30LU4-29 Specifications

| | |
|-------------------------------------------------------|--------------------------------------------------------------------|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.400 Inches Minimum And 0.450 Inches Maximum |
| Fastener Length: | 2.222 Inches Minimum And 2.252 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.455 Inches Minimum And 0.510 Inches Maximum |
| Grip Diameter: | 0.2485 Inches Minimum And 0.2495 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 1.802 Inches Minimum And 1.822 Inches Maximum |
| Thread Quantity Per Inch: | 28 |
| Countersink Angle: | 100.0 Degrees Nominal |
| Surface Finish: | 32.0 Microinches Grip |
| Surface Finish: | 32.0 Microinches Threads |
| Material: | Steel Comp E4340 Overall Or Steel Comp 8740 Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/BACB30LU4-29> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.