

Description

Fastener Length: 4-7/8", Thread: 1/4-28, Thread Length: 27/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30LU471
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-193-6181
National Motor Freight:	096630, Screws Noi Brass / Bronze / Copper

NO IMAGE
AVAILABLE

P/N BACB30LU4-71 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.425 Inches Nominal
Fastener Length:	4.848 Inches Minimum And 4.878 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.455 Inches Minimum And 0.510 Inches Maximum
Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.2500 Inches
Grip Length:	4.428 Inches Minimum And 4.448 Inches Maximum
Thread Quantity Per Inch:	28
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty2,cl2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/BACB30LU4-71> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.