

Description

Fastener Length: 1-3/8", Thread: 1/4-28, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30LU4D15
Minimum Qty (MOQ):	10 EA
NSN:	5305-01-268-0910
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N BACB30LU4D15 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.400 Inches Minimum And 0.450 Inches Maximum
Fastener Length:	1.348 Inches Minimum And 1.378 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.455 Inches Minimum And 0.510 Inches Maximum
Grip Diameter:	0.241 Inches Minimum And 0.244 Inches Maximum
Shank Unthreaded Hole Diameter:	0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.928 Inches Minimum And 0.948 Inches Maximum
Thread Quantity Per Inch:	28
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Distance From Head Largest Bearing Surface To Shank Hole Center:	1.170 Inches Minimum First Hole And 1.210 Inches Maximum First Hole
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjc

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/close+tolerance+bolts/BACB30LU4D15> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.