

P/N BACB30LU5-11

Description

Fastener Length: 1-11/64", Thread: 1/4-24, Thread Length: 0-63/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: BACB30LU511

Minimum Qty (MOQ): 15 EA

NSN: 5305-01-251-9258

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N BACB30LU5-11 Specifications

Thread Direction: Right-hand Thread Length: 0.920 Inches Minimum And 1.033 Inches Maximum Fastener Length: 1.142 Inches Minimum And 1.172 Inches Maximum Head Style: Flat Countersunk Head Diameter: 0.574 Inches Minimum And 0.637 Inches Maximum Grip Diameter: 0.3110 Inches Minimum And 0.3120 Inches Maximum Grip Diameter: 0.3110 Inches Minimum And 0.3120 Inches Maximum Internal Drive Style: Cross Recess Type 1 Nominal Thread Diameter: 0.312 Inches Grip Length: 0.678 Inches Minimum And 0.698 Inches Maximum Thread Quantity Per Inch: 24 Minimum Tensile Strength: 125000 Pounds Per Square Inch Countersink Angle: 99.0 Degrees Minimum And 10.0 Degrees Maximum Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Material Response Overall Or Mil-s-6049 Mil Spec 2nd		
Thread Length: 0,920 Inches Minimum And 1.033 Inches Maximum 1.142 Inches Minimum And 1.172 Inches Maximum Head Style: Head Diameter: 0,574 Inches Minimum And 0.637 Inches Maximum Grip Diameter: 0,3110 Inches Minimum And 0.3120 Inches Maximum Internal Drive Style: Cross Recess Type 1 Nominal Thread Diameter: 0,312 Inches Grip Length: 0,678 Inches Minimum And 0.698 Inches Maximum Thread Quantity Per Inch: 24 Minimum Tensile Strength: 125000 Pounds Per Square Inch Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall And Classification: Surface Treatment: Cadmium Overall And Chromate Overall Oq-p-416.ty 2 Cl 2 Fed Spec Single Treatment Response Overall	Thread Class:	3a
Fastener Length: 1.42 Inches Minimum And 1.172 Inches Maximum Head Style: Flat Countersunk Head Diameter: 0.574 Inches Minimum And 0.637 Inches Maximum Grip Diameter: 0.3110 Inches Minimum And 0.3120 Inches Maximum Internal Drive Style: Cross Recess Type 1 Nominal Thread Diameter: 0.312 Inches Grip Length: 0.678 Inches Minimum And 0.698 Inches Maximum Thread Quantity Per Inch: 24 Minimum Tensile Strength: 125000 Pounds Per Square Inch Countersink Angle: 99.0 Degrees Minimum And 10.1.0 Degrees Maximum Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Will-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall	Thread Direction:	Right-hand
Head Style: Flat Countersunk Head Diameter: 0.574 Inches Minimum And 0.637 Inches Maximum Grip Diameter: 0.3110 Inches Minimum And 0.3120 Inches Maximum Internal Drive Style: Cross Recess Type 1 Nominal Thread Diameter: 0.312 Inches Grip Length: 0.678 Inches Minimum And 0.698 Inches Maximum Thread Quantity Per Inch: 24 Minimum Tensile Strength: 125000 Pounds Per Square Inch Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall And Chromate Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Oq-p-416.ty 2 Cl 2 Fed Spec Single Treatment Response Overall	Thread Length:	0.920 Inches Minimum And 1.033 Inches Maximum
Head Diameter: 0.574 Inches Minimum And 0.637 Inches Maximum Grip Diameter: 0.3110 Inches Minimum And 0.3120 Inches Maximum Internal Drive Style: Cross Recess Type 1 Nominal Thread Diameter: 0.312 Inches Grip Length: 0.678 Inches Minimum And 0.698 Inches Maximum Thread Quantity Per Inch: 24 Minimum Tensile Strength: 125000 Pounds Per Square Inch Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall	Fastener Length:	1.142 Inches Minimum And 1.172 Inches Maximum
Grip Diameter: Internal Drive Style: Cross Recess Type 1 Nominal Thread Diameter: 0.312 Inches Grip Length: 0.678 Inches Minimum And 0.698 Inches Maximum Thread Quantity Per Inch: 24 Minimum Tensile Strength: 125000 Pounds Per Square Inch Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall	Head Style:	Flat Countersunk
Internal Drive Style: Nominal Thread Diameter: O.312 Inches Grip Length: O.678 Inches Minimum And 0.698 Inches Maximum Thread Quantity Per Inch: Minimum Tensile Strength: Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Threads Material: Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std Mil-s-5000 Mil Spec 1st Material Response Overall Cadmium Overall And Chromate Overall Oq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall	Head Diameter:	0.574 Inches Minimum And 0.637 Inches Maximum
Nominal Thread Diameter: Grip Length: 0.678 Inches Minimum And 0.698 Inches Maximum Thread Quantity Per Inch: 24 Minimum Tensile Strength: 125000 Pounds Per Square Inch Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Material Document And Classification: Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall	Grip Diameter:	0.3110 Inches Minimum And 0.3120 Inches Maximum
Grip Length: 0.678 Inches Minimum And 0.698 Inches Maximum Thread Quantity Per Inch: 24 Minimum Tensile Strength: 125000 Pounds Per Square Inch Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall Surface Treatment: Surface Treatment Document And Classification: Surface Treatment Document And Classification: Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall	Internal Drive Style:	Cross Recess Type 1
Thread Quantity Per Inch: Minimum Tensile Strength: 125000 Pounds Per Square Inch Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall	Nominal Thread Diameter:	0.312 Inches
Minimum Tensile Strength: 125000 Pounds Per Square Inch 99.0 Degrees Minimum And 101.0 Degrees Maximum 32.0 Microinches Bearing Surface Of Head 32.0 Microinches Bearing Surface Of Head 32.0 Microinches Threads Surface Finish: 32.0 Microinches Threads Steel Comp E4340 Overall Or Steel Comp 8740 Overall Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall	Grip Length:	0.678 Inches Minimum And 0.698 Inches Maximum
Countersink Angle: 99.0 Degrees Minimum And 101.0 Degrees Maximum 32.0 Microinches Bearing Surface Of Head 32.0 Microinches Threads Surface Finish: 32.0 Microinches Threads Steel Comp E4340 Overall Or Steel Comp 8740 Overall Material: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Operation: Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall	Thread Quantity Per Inch:	24
Surface Finish: 32.0 Microinches Bearing Surface Of Head 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall	Minimum Tensile Strength:	125000 Pounds Per Square Inch
Surface Finish: Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall	Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material: Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall	Surface Finish:	32.0 Microinches Bearing Surface Of Head
Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall Cadmium Overall And Chromate Overall Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-604	Surface Finish:	32.0 Microinches Threads
Material Document And Classification: 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall	Material:	Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Surface Treatment Document And Classification: Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall	Material Document And Classification:	
Classification: Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall	Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Series Designator: Unif	Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall
· ·	Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/close+tolerance+screws/BACB30LU5-11 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.