

**Description**

Fastener Length: 63/64", Thread: 1/4-24, Thread Length: 31/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                                           |
|-------------------------|-------------------------------------------|
| SKU / Model:            | BACB30LU58                                |
| Minimum Qty (MOQ):      | 5 EA                                      |
| NSN:                    | 5305-01-136-7149                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N BACB30LU5-8 Specifications

|                                                       |                                                                                                                                                           |
|-------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Thread Class:</b>                                  | 3a                                                                                                                                                        |
| <b>Thread Direction:</b>                              | Right-hand                                                                                                                                                |
| <b>Thread Length:</b>                                 | 0.444 Inches Minimum And 0.494 Inches Maximum                                                                                                             |
| <b>Fastener Length:</b>                               | 0.954 Inches Minimum And 0.984 Inches Maximum                                                                                                             |
| <b>Head Style:</b>                                    | Flat Countersunk                                                                                                                                          |
| <b>Head Diameter:</b>                                 | 0.574 Inches Minimum And 0.637 Inches Maximum                                                                                                             |
| <b>Grip Diameter:</b>                                 | 0.3110 Inches Minimum And 0.3120 Inches Maximum                                                                                                           |
| <b>Internal Drive Style:</b>                          | Cross Recess Type 1                                                                                                                                       |
| <b>Nominal Thread Diameter:</b>                       | 0.312 Inches                                                                                                                                              |
| <b>Grip Length:</b>                                   | 0.490 Inches Minimum And 0.510 Inches Maximum                                                                                                             |
| <b>Thread Quantity Per Inch:</b>                      | 24                                                                                                                                                        |
| <b>Countersink Angle:</b>                             | 99.0 Degrees Minimum And 101.0 Degrees Maximum                                                                                                            |
| <b>Surface Finish:</b>                                | 32.0 Microinches Grip                                                                                                                                     |
| <b>Surface Finish:</b>                                | 32.0 Microinches Threads                                                                                                                                  |
| <b>Material:</b>                                      | Steel Comp E4340 Overall Or Steel Comp 8740 Overall Or Steel Comp 8740 Overall                                                                            |
| <b>Material Document And Classification:</b>          | Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 3rd Material Response Overall |
| <b>Surface Treatment:</b>                             | Cadmium Overall And Chromate Overall                                                                                                                      |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416 Ty 2 Class 2 Fed Spec Single Treatment Response Overall                                                                                          |
| <b>Thread Series Designator:</b>                      | Unjf                                                                                                                                                      |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/BACB30LU5-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.