

P/N BACB30LU7-35

Description

Fastener Length: 2-57/64", Thread: 7/16-20, Thread Length: 11/16"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: BACB30LU735

Minimum Qty (MOQ): 1 EA

NSN: 5305-01-435-3850

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 096640, Screws, Iron Or Steel



^{*} See page 2 for technical characteristics

P/N BACB30LU7-35 Specifications

Thread Class:	3a
inread Class:	
Thread Direction:	Right-hand
Thread Length:	0.694 Inches Nominal
Fastener Length:	2.8665 Inches Minimum And 2.8965 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.809 Inches Minimum And 0.892 Inches Maximum
Grip Diameter:	0.4360 Inches Minimum And 0.4370 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.4375 Inches
Grip Length:	2.1775 Inches Minimum And 2.1975 Inches Maximum
Thread Quantity Per Inch:	20
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416, Type 2 Class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/close+tolerance+screws/BACB30LU7-35 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.