



Military-Fasteners.com

P/N BACB30LU7-39

Description

Fastener Length: 3-9/64", Thread: 7/16-20, Thread Length: 11/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30LU739
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-435-3878
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N BACB30LU7-39 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.694 Inches Nominal
Fastener Length:	3.1165 Inches Minimum And 3.1465 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.809 Inches Minimum And 0.892 Inches Maximum
Grip Diameter:	0.4360 Inches Minimum And 0.4370 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.4375 Inches
Grip Length:	2.4275 Inches Minimum And 2.4475 Inches Maximum
Thread Quantity Per Inch:	20
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Comp E2 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416, Type 2 Class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/BACB30LU7-39> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.