

## P/N BACB30LU8-54

## **Description**

Fastener Length: 4-1/8", Thread: 1/2-20, Thread Length: 47/64"

\* Manufacturer certifications are shipped with your order FREE of charge

### Order this part online

#### **Additional Information**

SKU / Model: BACB30LU854

Minimum Qty (MOQ): 5 EA

NSN: 5305-01-435-5829

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# **P/N BACB30LU8-54 Specifications**

Thread Class:	За
Thread Direction:	Right-hand
Thread Length:	0.735 Inches Nominal
Fastener Length:	4.0950 Inches Minimum And 4.1250 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.927 Inches Minimum And 1.019 Inches Maximum
Grip Diameter:	0.4985 Inches Minimum And 0.4995 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.5000 Inches
Grip Length:	3.3650 Inches Minimum And 3.3850 Inches Maximum
Thread Quantity Per Inch:	20
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416, Type 2 Class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

## **How to Order**

Order this screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/close+tolerance+screws/BACB30LU8-54">https://military-fasteners.com/screws/close+tolerance+screws/BACB30LU8-54</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.