

Description

Fastener Length: 1/2", Thread Size: 5/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	BACB30MB5A3
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-531-2951
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE
AVAILABLE

P/N BACB30MB5A3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.490 Inches Minimum And 0.510 Inches Maximum
Head Style:	Straight Pan
Head Height:	0.055 Inches Minimum And 0.065 Inches Maximum
Width Between Flats:	0.079 Inches Minimum And 0.080 Inches Maximum
Shank Diameter:	0.163 Inches Minimum And 0.164 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.306 Inches Minimum And 0.322 Inches Maximum
Lubrication:	Cetyl Alcohol
End Item Identification:	B-52 Aircraft
Grip Length:	0.183 Inches Minimum And 0.193 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Size:	0.164 Inches
Shear Strength:	95000 Single Pounds Per Square Inch
Part Name Assigned By Controlling Agency:	Bolt, Protruding Head, Hex Drive, Tension
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,type II,class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjc

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30MB5A3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.