

Description

Fastener Length: 3/4", Thread Size: 5/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30MB5A7SU
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-355-1476
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed



* See page 2 for technical characteristics

P/N BACB30MB5A7SU Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.7395 Inches Minimum And 0.7595 Inches Maximum
Head Style:	Err-090
Head Height:	0.0550 Inches Minimum And 0.0650 Inches Maximum
Width Between Flats:	0.0791 Inches Minimum And 0.0801 Inches Maximum
Shank Diameter:	0.1630 Inches Minimum And 0.1635 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.3060 Inches Minimum And 0.3220 Inches Maximum
Lubrication:	Dry Film
Grip Length:	0.4325 Inches Minimum And 0.4425 Inches Maximum
Thread Quantity Per Inch:	32
Nominal Thread Size:	0.1640 Inches
Shear Strength:	95000 Single Pounds Per Square Inch
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Amsams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjc

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30MB5A7SU> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.