

Description

3a thread class

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30MC68
Minimum Qty (MOQ):	10
NSN:	5320-00-113-3890
ECCN:	EAR99
National Motor Freight:	095190, Hardware, Noi



* See page 2 for technical characteristics

P/N BACB30MC6-8 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.815 Inches Minimum And 0.835 Inches Maximum
Width Between Flats:	0.079 Inches Minimum And 0.081 Inches Maximum
Shank Diameter:	0.202 Inches Minimum And 0.203 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Grip Length:	0.495 Inches Minimum And 0.505 Inches Maximum
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Nominal Thread Size:	0.190 Inches
Shear Strength:	95000 Single Pounds Per Square Inch
Material:	Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6758 Mil Spec 3rd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this pin-rivet from our inventory online by visiting https://military-fasteners.com/pins/pin_rivets/BACB30MC6-8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.