

Description

Fastener Length: 1/2", Thread Size: 5/32"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	BACB30ND5A3
Minimum Qty (MOQ):	1 EA
NSN:	5320-01-429-3024
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	096320, Rivets I / S Nickel Plated Buffed

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N BACB30ND5A3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Fastener Length:	0.490 Inches Minimum And 0.510 Inches Maximum
Head Style:	Flush Countersunk
Width Between Flats:	0.0791 Inches Minimum And 0.0801 Inches Maximum
Shank Diameter:	0.1625 Inches Minimum And 0.1635 Inches Maximum
Shank Style:	Pin-rivet, Straight, Threaded
Head Major Diameter:	0.2874 Inches Minimum And 0.2922 Inches Maximum
Grip Length:	0.183 Inches Minimum And 0.193 Inches Maximum
Nominal Thread Size:	0.164 Inches
Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall
Material Document And Classification:	Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6758 Mil Spec 3rd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416, Ty 2, Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjc

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30ND5A3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.