

P/N BACB30NE3-11

Description

Fastener Length: 1-3/64", Thread: 10-32, Thread Length: 23/64

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: BACB30NE311

Minimum Qty (MOQ): 100

NSN: 5306-01-108-8374

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N BACB30NE3-11 Specifications

Thread Direction: Right-hand 0.320 Inches Minimum And 0.370 Inches Maximum Fastener Length: 1.018 Inches Minimum And 1.048 Inches Maximum Head Style: Dished Hexagon Head Height: 0.110 Inches Minimum And 0.125 Inches Maximum Width Between Flats: 0.367 Inches Minimum And 0.1895 Inches Maximum Grip Diameter: 0.1885 Inches Minimum And 0.1895 Inches Maximum Nominal Thread Diameter: 0.190 Inches Grip Length: 0.678 Inches Minimum And 0.698 Inches Maximum Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Mils-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std		
Thread Length: 0.320 Inches Minimum And 0.370 Inches Maximum 1.018 Inches Minimum And 1.048 Inches Maximum Dished Hexagon Head Style: 0.110 Inches Minimum And 0.125 Inches Maximum Width Between Flats: 0.367 Inches Minimum And 0.376 Inches Maximum Width Between Flats: 0.367 Inches Minimum And 0.376 Inches Maximum Grip Diameter: 0.1885 Inches Minimum And 0.1895 Inches Maximum Nominal Thread Diameter: 0.190 Inches Grip Length: 0.678 Inches Minimum And 0.698 Inches Maximum Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Threads Material: Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std	Thread Class:	3a
Fastener Length: 1.018 Inches Minimum And 1.048 Inches Maximum Dished Hexagon 0.110 Inches Minimum And 0.125 Inches Maximum Width Between Flats: 0.367 Inches Minimum And 0.376 Inches Maximum Grip Diameter: 0.1885 Inches Minimum And 0.1895 Inches Maximum Nominal Thread Diameter: 0.190 Inches Grip Length: 0.678 Inches Minimum And 0.698 Inches Maximum Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Threads Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std	Thread Direction:	Right-hand
Head Style: Dished Hexagon 0.110 Inches Minimum And 0.125 Inches Maximum Width Between Flats: 0.367 Inches Minimum And 0.376 Inches Maximum Grip Diameter: 0.1885 Inches Minimum And 0.1895 Inches Maximum Nominal Thread Diameter: 0.190 Inches Grip Length: 0.678 Inches Minimum And 0.698 Inches Maximum Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material Document And Classification: Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std	Thread Length:	0.320 Inches Minimum And 0.370 Inches Maximum
Head Height: 0.110 Inches Minimum And 0.125 Inches Maximum Width Between Flats: 0.367 Inches Minimum And 0.376 Inches Maximum Grip Diameter: 0.1885 Inches Minimum And 0.1895 Inches Maximum Nominal Thread Diameter: 0.190 Inches Grip Length: 0.678 Inches Minimum And 0.698 Inches Maximum Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std	Fastener Length:	1.018 Inches Minimum And 1.048 Inches Maximum
Width Between Flats: 0.367 Inches Minimum And 0.376 Inches Maximum O.1885 Inches Minimum And 0.1895 Inches Maximum Nominal Thread Diameter: 0.190 Inches Grip Length: 0.678 Inches Minimum And 0.698 Inches Maximum Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std	Head Style:	Dished Hexagon
Grip Diameter: Nominal Thread Diameter: 0.190 Inches Grip Length: 0.678 Inches Minimum And 0.698 Inches Maximum Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std	Head Height:	0.110 Inches Minimum And 0.125 Inches Maximum
Nominal Thread Diameter: 0.190 Inches 0.678 Inches Minimum And 0.698 Inches Maximum Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std	Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Grip Length: O.678 Inches Minimum And O.698 Inches Maximum Thread Quantity Per Inch: 32 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std	Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Thread Quantity Per Inch: Minimum Tensile Strength: 160000 Pounds Per Square Inch 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std	Nominal Thread Diameter:	0.190 Inches
Minimum Tensile Strength: 160000 Pounds Per Square Inch 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Steel Comp E4340 Overall Or Steel Comp 8740 Overall Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std	Grip Length:	0.678 Inches Minimum And 0.698 Inches Maximum
Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Surface Finish: 32.0 Microinches Bearing Surface Of Head 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Surface Finish: 32.0 Microinches Threads Steel Comp E4340 Overall Or Steel Comp 8740 Overall Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std	Thread Quantity Per Inch:	32
Surface Finish: 32.0 Microinches Bearing Surface Of Head 32.0 Microinches Grip 32.0 Microinches Grip 32.0 Microinches Threads 32.0 Microinches Threads Steel Comp E4340 Overall Or Steel Comp 8740 Overall Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Surface Finish: Surface Finish: 32.0 Microinches Grip 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std	Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std	Surface Finish:	32.0 Microinches Bearing Surface Of Head
Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std	Surface Finish:	32.0 Microinches Grip
Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std	Surface Finish:	32.0 Microinches Threads
Material Document And Classification:	Material:	Steel Comp E4340 Overall Or Steel Comp 8740 Overall
	Material Document And Classification:	
Surface Treatment: Cadmium Overall And Chromate Overall	Surface Treatment:	Cadmium Overall And Chromate Overall
Og-n-416 type 2 class 2 Fed Spec Single Treatment Response Overall	Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator: Unjf	Thread Series Designator:	Unjf
Specification/standard Data: 80205-nas6603 Professional/industrial Association Standard	Specification/standard Data:	80205-nas6603 Professional/industrial Association Standard

How to Order

Order this machine bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/BACB30NE3-11 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.