

P/N BACB30NE4D7

Description

Fastener Length: 7/8", Thread: 1/4-28, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: BACB30NE4D7

Minimum Qty (MOQ): 5 EA

NSN: 5306-01-194-0602

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N BACB30NE4D7 Specifications

Thread Direction: Right-hand O.400 Inches Minimum And 0.450 Inches Maximum Fastener Length: 0.848 Inches Minimum And 0.878 Inches Maximum Head Style: Dished Hexagon Head Height: 0.125 Inches Minimum And 0.140 Inches Maximum Width Between Flats: 0.429 Inches Minimum And 0.439 Inches Maximum Grip Diameter: 0.2485 Inches Minimum And 0.2495 Inches Maximum Shank Unthreaded Hole Diameter: 0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole Nominal Thread Diameter: 0.250 Inches	Thursd Class.	24
Thread Length: 0.400 Inches Minimum And 0.450 Inches Maximum Fastener Length: 0.848 Inches Minimum And 0.878 Inches Maximum Head Style: Dished Hexagon Head Height: 0.125 Inches Minimum And 0.140 Inches Maximum Width Between Flats: 0.429 Inches Minimum And 0.439 Inches Maximum Grip Diameter: 0.2485 Inches Minimum And 0.2495 Inches Maximum Shank Unthreaded Hole Diameter: 0.250 Inches Nominal Thread Diameter: 0.250 Inches Orip Length: 0.428 Inches Minimum And 0.448 Inches Maximum First Hole Nominal Thread Diameter: 0.250 Inches Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Surface Treatment: Cadmun Overall And Chormate Overall Thread Series Designator: Unjf	Thread Class:	3a
Fastener Leight: 0.848 Inches Minimum And 0.878 Inches Maximum Head Style: Dished Hexagon Head Height: 0.125 Inches Minimum And 0.140 Inches Maximum Width Between Flats: 0.429 Inches Minimum And 0.439 Inches Maximum Grip Diameter: 0.2485 Inches Minimum And 0.2495 Inches Maximum Shank Unthreaded Hole Diameter: 0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole Nominal Thread Diameter: 0.250 Inches Grip Length: 0.428 Inches Minimum And 0.448 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material Document And Classification: 32.0 Microinches Threads Material Document And Classification: Ams6322 Assn Std 2nd Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mi	Thread Direction:	Right-hand
Head Style: Dished Hexagon Head Height: 0.125 Inches Minimum And 0.140 Inches Maximum Width Between Flats: 0.429 Inches Minimum And 0.439 Inches Maximum Grip Diameter: 0.2485 Inches Minimum And 0.2495 Inches Maximum Shank Unthreaded Hole Diameter: 0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole Nominal Thread Diameter: 0.250 Inches Grip Length: 0.428 Inches Minimum First Hole And 0.086 Inches Maximum First Hole Minimum Tensile Strength: 1.60000 Pounds Per Square Inch Hardness Rating: 1.60000 Po	Thread Length:	0.400 Inches Minimum And 0.450 Inches Maximum
Head Height: 0.125 Inches Minimum And 0.140 Inches Maximum Width Between Flats: 0.429 Inches Minimum And 0.439 Inches Maximum Grip Diameter: 0.2485 Inches Minimum And 0.2495 Inches Maximum Shank Unthreaded Hole Diameter: 0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole Nominal Thread Diameter: 0.250 Inches Grip Length: 0.428 Inches Minimum And 0.448 Inches Maximum First Hole Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: 52.0 Microinches Threads Material Document And Classification: Mili-s-5000 Mil Spec 1st Material Response Overall Or Mili-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Surface Treatment: 0camimum And Classification: Q-p-416,ty2,cl2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unjf	Fastener Length:	0.848 Inches Minimum And 0.878 Inches Maximum
Width Between Flats: O.429 Inches Minimum And 0.439 Inches Maximum Orip Diameter: O.2485 Inches Minimum And 0.2495 Inches Maximum Shank Unthreaded Hole Diameter: O.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole Nominal Thread Diameter: O.250 Inches Grip Length: O.428 Inches Minimum And 0.448 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: Hardness Rating: O.680 O Pounds Per Square Inch Hardness Rating: O.680 Inches Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: Surface Finish: Surface Finish: 3.0 Microinches Bearing Surface Of Head Surface Finish: 3.1 Microinches Grip Surface Finish: 3.2 Microinches Threads Material: Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Thread Series Designator: Unjf	Head Style:	Dished Hexagon
Grip Diameter: 0.2485 Inches Minimum And 0.2495 Inches Maximum Shank Unthreaded Hole Diameter: 0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole Nominal Thread Diameter: 0.250 Inches Grip Length: 0.428 Inches Minimum And 0.448 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: 5teel Comp E4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Thread Series Designator: Unjf	Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Shank Unthreaded Hole Diameter: 0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole Nominal Thread Diameter: 0.250 Inches Grip Length: 0.428 Inches Minimum And 0.448 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 0.680 Inches Minimum First Hole And 0.690 Inches Maximum First Hole Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material Document And Classification: 5teel Comp E4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty2,cl2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unjf	Width Between Flats:	0.429 Inches Minimum And 0.439 Inches Maximum
Nominal Thread Diameter: Grip Length: 0.428 Inches Minimum And 0.448 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: 32.0 Microinches Threads Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty2,cl2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unjf	Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Grip Length: O.428 Inches Minimum And O.448 Inches Maximum Thread Quantity Per Inch: Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Surface Treatment: Surface Treatment Document And Classification: Q-p-416,ty2,cl2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unjf	Shank Unthreaded Hole Diameter:	0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole
Thread Quantity Per Inch: Minimum Tensile Strength: Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Distance From Head Largest Bearing Surface To Shank Hole Center: Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Thread Series Designator: Unjf	Nominal Thread Diameter:	0.250 Inches
Minimum Tensile Strength: Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall 0.680 Inches Minimum First Hole And 0.690 Inches Maximum First Hole Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty2,cl2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unjf	Grip Length:	0.428 Inches Minimum And 0.448 Inches Maximum
Hardness Rating: Distance From Head Largest Bearing Surface To Shank Hole Center: Surface Finish: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Mill-s-5000 Mil Spec 1st Material Response Overall Or Mill-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Thread Series Designator: Unjf	Thread Quantity Per Inch:	28
Distance From Head Largest Bearing Surface To Shank Hole Center: Surface Finish: Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Thread Series Designator: Unjf	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Shank Hole Center: Surface Finish: Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty2,cl2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unjf	Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Surface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Steel Comp E4340 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416,ty2,cl2 Fed Spec Single Treatment Response OverallThread Series Designator:Unjf		0.680 Inches Minimum First Hole And 0.690 Inches Maximum First Hole
Surface Finish: Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty2,cl2 Fed Spec Single Treatment Response Overall Unjf	Surface Finish:	32.0 Microinches Bearing Surface Of Head
Material:Steel Comp E4340 Overall Or Steel Comp 8740 OverallMaterial Document And Classification:Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response OverallSurface Treatment:Cadmium Overall And Chromate OverallSurface Treatment Document And Classification:Qq-p-416,ty2,cl2 Fed Spec Single Treatment Response OverallThread Series Designator:Unjf	Surface Finish:	32.0 Microinches Grip
Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty2,cl2 Fed Spec Single Treatment Response Overall Unjf	Surface Finish:	32.0 Microinches Threads
Material Document And Classification: Ams6322 Assn Std 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty2,cl2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unjf	Material:	Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Surface Treatment Document And Classification: Qq-p-416,ty2,cl2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unjf	Material Document And Classification:	
Thread Series Designator: Unjf	Surface Treatment:	Cadmium Overall And Chromate Overall
	Surface Treatment Document And Classification:	Qq-p-416,ty2,cl2 Fed Spec Single Treatment Response Overall
Specification/standard Data: 80205-nas6604 Professional/industrial Association Standard	Thread Series Designator:	Unjf
	Specification/standard Data:	80205-nas6604 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/BACB30NE4D7 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/BACB30NE4D7 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/BACB30NE4D7 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/BACB30NE4D7 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/BACB30NE4D7 and selecting the quantity you want then click "add to cart".