

## P/N BACB30NE4H3

### **Description**

Fastener Length: 5/8", Thread: 1/4-28, Thread Length: 7/16"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: BACB30NE4H3

Minimum Qty (MOQ): 1 EA

NSN: 5306-01-053-6965

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# **P/N BACB30NE4H3 Specifications**

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.400 Inches Minimum And 0.450 Inches Maximum
Fastener Length:	0.598 Inches Minimum And 0.628 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.178 Inches Minimum And 0.198 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

## **How to Order**

Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/BACB30NE4H3">https://military-fasteners.com/bolts/machine+bolts/BACB30NE4H3</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.