

**Description**

Fastener Length: 1-41/64", Thread: 1/4-28, Thread Length: 13/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	BACB30NF419
Minimum Qty (MOQ):	10 EA
NSN:	5306-01-483-1375



## P/N BACB30NF4-19 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.364 Inches Minimum And 0.414 Inches Maximum
<b>Fastener Length:</b>	1.624 Inches Minimum And 1.654 Inches Maximum
<b>Head Style:</b>	Undercut Hexagon
<b>Head Height:</b>	0.125 Inches Minimum And 0.140 Inches Maximum
<b>Width Between Flats:</b>	0.430 Inches Minimum And 0.439 Inches Maximum
<b>Grip Diameter:</b>	0.2485 Inches Minimum And 0.2495 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Grip Length:</b>	1.178 Inches Minimum And 1.198 Inches Maximum
<b>Thread Quantity Per Inch:</b>	28
<b>Minimum Tensile Strength:</b>	140000 Pounds Per Square Inch
<b>Surface Finish:</b>	32.0 Microinches Bearing Surface Of Head
<b>Surface Finish:</b>	32.0 Microinches Grip
<b>Surface Finish:</b>	32.0 Microinches Threads
<b>Material:</b>	Steel Comp E4340 Overall Or Steel Comp 8740 Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30NF4-19> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.