

Description

Fastener Length: 2-13/64", Thread: 1/4-28, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30NF429
Minimum Qty (MOQ):	35 EA
NSN:	5306-01-371-2852



P/N BACB30NF4-29 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.389 Inches Maximum
Fastener Length:	2.187 Inches Minimum And 2.217 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Width Between Flats:	0.430 Inches Minimum And 0.438 Inches Maximum
Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Shank Unthreaded Hole Diameter:	0.076 Inches Minimum Threads And 0.086 Inches Maximum Threads
Nominal Thread Diameter:	0.250 Inches
Grip Length:	1.803 Inches Minimum And 1.823 Inches Maximum
Thread Quantity Per Inch:	28
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Distance From Head Largest Bearing Surface To Shank Hole Center:	2.071 Inches Minimum Threads And 2.101 Inches Maximum Threads
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30NF4-29> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.