

## Description

Fastener Length: 2-13/64", Thread: 1/4-28, Thread Length: 3/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	BACB30NF429
Minimum Qty (MOQ):	35 EA
NSN:	5306-01-371-2852



## P/N BACB30NF4-29 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.389 Inches Maximum
<b>Fastener Length:</b>	2.187 Inches Minimum And 2.217 Inches Maximum
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.125 Inches Minimum And 0.140 Inches Maximum
<b>Width Between Flats:</b>	0.430 Inches Minimum And 0.438 Inches Maximum
<b>Grip Diameter:</b>	0.2485 Inches Minimum And 0.2495 Inches Maximum
<b>Shank Unthreaded Hole Diameter:</b>	0.076 Inches Minimum Threads And 0.086 Inches Maximum Threads
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Grip Length:</b>	1.803 Inches Minimum And 1.823 Inches Maximum
<b>Thread Quantity Per Inch:</b>	28
<b>Hardness Rating:</b>	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
<b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b>	2.071 Inches Minimum Threads And 2.101 Inches Maximum Threads
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30NF4-29> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.