

P/N BACB30NF4-32

Description

Fastener Length: 2-3/8", Thread: 1/4-28, Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: BACB30NF432

Minimum Qty (MOQ): 5 EA

NSN: 5306-01-524-7134



^{*} See page 2 for technical characteristics

P/N BACB30NF4-32 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.389 Inches Nominal
Fastener Length:	2.389 Inches Nominal
Head Style:	Dished Hexagon
Head Diameter:	2.389 Inches Nominal
Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	2.000 Inches Nominal
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	140000 Pounds Per Square Inch
Material:	Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Ams 6415 Assn Std 1st Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Tyii, Cl2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/BACB30NF4-32 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.