

Description

Fastener Length: 1-5/16", Thread: 1/4-28, Thread Length: 27/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30NF4D14
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-308-2849
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N BACB30NF4D14 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.425 Inches Nominal
Fastener Length:	1.285 Inches Minimum And 1.315 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Grip Diameter:	0.2481 Inches Minimum And 0.2487 Inches Maximum
Single Shear Strength:	95000 Pounds Per Square Inch
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.865 Inches Minimum And 0.885 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Steel Comp 4340 Overall
Material Document And Classification:	Mil-s-5000 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6604d14 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30NF4D14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.