

P/N BACB30NF4D27

Description

Fastener Length: 2-5/64", Hole Diameter: 3/64", Thread: 1/4-28, Thread Length: 13/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: BACB30NF4D27

Minimum Qty (MOQ): 1 EA

NSN: 5306-01-049-4047

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N BACB30NF4D27 Specifications

3a
Right-hand
0.364 Inches Minimum And 0.414 Inches Maximum
2.062 Inches Minimum And 2.092 Inches Maximum
Undercut Hexagon
0.125 Inches Minimum And 0.140 Inches Maximum
0.430 Inches Minimum And 0.439 Inches Maximum
0.051 Inches Nominal
0.2485 Inches Minimum And 0.2495 Inches Maximum
0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole
Aircraft, Stratolifter C-135;e-3a Awacs
0.250 Inches
1.678 Inches Minimum And 1.698 Inches Maximum
3
Drilled
28
140000 Pounds Per Square Inch
Hexagon Longitudinal Hole
1.936 Inches Minimum First Hole And 1.986 Inches Maximum First Hole
32.0 Microinches Bearing Surface Of Head
32.0 Microinches Grip
32.0 Microinches Threads
Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Cadmium Overall And Chromate Overall
Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall
Unjf
81205-bacb30nf Manufacturers Standard

How to Order

