

P/N BACB30NF5-11

Description

Fastener Length: 1-3/16", Thread: 1/4-24, Thread Length: 31/64"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: BACB30NF511

Minimum Qty (MOQ): 1 EA

NSN: 5306-01-142-0305

Schedule B: 7318.15.2010

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N BACB30NF5-11 Specifications

Thread Direction: Right-hand Thread Length: 0.444 Inches Minimum And 0.494 Inches Maximum Fastener Length: 1.142 Inches Minimum And 1.192 Inches Maximum Head Style: Dished Hexagon Head Height: 0.156 Inches Minimum And 0.171 Inches Maximum Width Between Flats: 0.492 Inches Minimum And 0.502 Inches Maximum Width Between Flats: 0.3110 Inches Minimum And 0.502 Inches Maximum Nominal Thread Diameter: 0.3110 Inches Minimum And 0.3120 Inches Maximum Nominal Thread Diameter: 0.312 Inches Grip Length: 0.678 Inches Minimum And 0.698 Inches Maximum Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Grip Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Mili-s-5000 Mil Spec 1st Material Response Overall Or Mili-s-6049 Mil Spec 2nd Material Response Overall Or Material Response Overall Or Mili-s-6049 Mil Spec 2nd Material Response Overall Or Material Response Overall Or Mili-s-6049 Mil Spec 2nd Material Response Overall Or Material Response Overall Or Mili-s-6049 Mil Spec 2nd Material Response Overall Or Material Response Overall Or Mili-s-6049 Mili		
Thread Length: 1.142 Inches Minimum And 0.494 Inches Maximum 1.142 Inches Minimum And 1.192 Inches Maximum Head Style: Dished Hexagon Head Height: 0.156 Inches Minimum And 0.171 Inches Maximum Width Between Flats: 0.492 Inches Minimum And 0.502 Inches Maximum Grip Diameter: 0.3110 Inches Minimum And 0.3120 Inches Maximum Osile Maximum Nominal Thread Diameter: 0.3112 Inches Grip Length: 0.678 Inches Minimum And 0.698 Inches Maximum Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Mill-s-5000 Mill Spec 1st Material Response Overall Material Document And Classification: Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Cadmium Overall And Chromate Overall Thread Series Designator: Unjf	Thread Class:	3a
Fastener Length: 1.142 Inches Minimum And 1.192 Inches Maximum Head Style: Dished Hexagon Head Height: 0.156 Inches Minimum And 0.171 Inches Maximum Width Between Flats: 0.492 Inches Minimum And 0.502 Inches Maximum Grip Diameter: 0.3110 Inches Minimum And 0.3120 Inches Maximum Nominal Thread Diameter: 0.312 Inches Grip Length: 0.678 Inches Minimum And 0.698 Inches Maximum Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Mili-s-5000 Mil Spec 1st Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Q-p-416.ty 2.cl 2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unjf	Thread Direction:	Right-hand
Head Style: Head Height: 0.156 Inches Minimum And 0.171 Inches Maximum Width Between Flats: 0.492 Inches Minimum And 0.502 Inches Maximum Grip Diameter: 0.3110 Inches Minimum And 0.3120 Inches Maximum Nominal Thread Diameter: 0.312 Inches Grip Length: 0.678 Inches Minimum And 0.698 Inches Maximum Thread Quantity Per Inch: 4 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Material Document And Classification: Mili-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Thread Series Designator: Unjf	Thread Length:	0.444 Inches Minimum And 0.494 Inches Maximum
Head Height: 0.156 Inches Minimum And 0.171 Inches Maximum Width Between Flats: 0.492 Inches Minimum And 0.502 Inches Maximum Grip Diameter: 0.3110 Inches Minimum And 0.3120 Inches Maximum Nominal Thread Diameter: 0.312 Inches Grip Length: 0.678 Inches Minimum And 0.698 Inches Maximum Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: 40 Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Material Response Overall Or Mil-s-6049 Mil Spec 2nd	Fastener Length:	1.142 Inches Minimum And 1.192 Inches Maximum
Width Between Flats: 0.492 Inches Minimum And 0.502 Inches Maximum Ominal Thread Diameter: 0.3110 Inches Minimum And 0.3120 Inches Maximum Nominal Thread Diameter: 0.312 Inches Grip Length: 0.678 Inches Minimum And 0.698 Inches Maximum Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Thread Series Designator: Unjf	Head Style:	Dished Hexagon
Grip Diameter: 0.3110 Inches Minimum And 0.3120 Inches Maximum Nominal Thread Diameter: 0.312 Inches 0.678 Inches Minimum And 0.698 Inches Maximum Thread Quantity Per Inch: 24 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall And Chromate Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Thread Series Designator: Unjf	Head Height:	0.156 Inches Minimum And 0.171 Inches Maximum
Nominal Thread Diameter: Grip Length: 0.678 Inches Minimum And 0.698 Inches Maximum Thread Quantity Per Inch: 44 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Unjf	Width Between Flats:	0.492 Inches Minimum And 0.502 Inches Maximum
Grip Length: 0.678 Inches Minimum And 0.698 Inches Maximum Thread Quantity Per Inch: 4 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Qq-p-416.ty 2,cl 2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unjf	Grip Diameter:	0.3110 Inches Minimum And 0.3120 Inches Maximum
Thread Quantity Per Inch: Minimum Tensile Strength: 160000 Pounds Per Square Inch 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Thread Series Designator: Unjf	Nominal Thread Diameter:	0.312 Inches
Minimum Tensile Strength: 160000 Pounds Per Square Inch 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Steel Comp E4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Thread Series Designator: Unjf	Grip Length:	0.678 Inches Minimum And 0.698 Inches Maximum
Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall Surface Finish: 32.0 Microinches Bearing Surface Of Head Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall Unjf	Thread Quantity Per Inch:	24
Surface Finish: Surface Finish: 32.0 Microinches Bearing Surface Of Head 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Surface Treatment: Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unjf	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Surface Finish: Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unjf	Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Surface Finish: Material: Steel Comp E4340 Overall Or Steel Comp 8740 Overall Material Document And Classification: Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Thread Series Designator: Unjf	Surface Finish:	32.0 Microinches Bearing Surface Of Head
Material: Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Surface Treatment: Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Thread Series Designator: Unjf	Surface Finish:	32.0 Microinches Grip
Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Cadmium Overall And Chromate Overall Surface Treatment Document And Classification: Classification: Thread Series Designator: Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-	Surface Finish:	32.0 Microinches Threads
Surface Treatment Document And Classification: Surface Treatment Document And Classification: Classification: Classification: Classification: Classification: Classification: Unjf Classification: Cadmium Overall And Chromate Overall Classification: Unjf	Material:	Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Surface Treatment Document And Classification: Thread Series Designator: Unjf Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall Unjf	Material Document And Classification:	
Classification: Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall Thread Series Designator: Unjf	Surface Treatment:	Cadmium Overall And Chromate Overall
	Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Constitution (at a dead Date)	Thread Series Designator:	Unjf
Specification/standard Data: 80205-nasobos Professional/Industrial Association Standard	Specification/standard Data:	80205-nas6605 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/BACB30NF5-11 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/BACB30NF5-11 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/BACB30NF5-11 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/BACB30NF5-11 and selecting the quantity you want then click "add to cart".