

Description

Fastener Length: 1-37/64", Hole Diameter: 5/16", Thread: 1/4-24, Thread Length: 31/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30NF519
Minimum Qty (MOQ):	15 EA
NSN:	5306-01-528-6952
Schedule B:	7318.15.8085
ECCN:	EAR99



* See page 2 for technical characteristics

P/N BACB30NF5-19 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.444 Inches Minimum And 0.494 Inches Maximum
Fastener Length:	1.569 Inches Minimum And 1.589 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.156 Inches Minimum And 0.171 Inches Maximum
Width Between Flats:	0.492 Inches Minimum And 0.502 Inches Maximum
Hole Diameter:	0.3110 Inches Minimum And 0.3120 Inches Maximum
Grip Diameter:	0.311 Inches Nominal
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.950 Inches Nominal
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	16000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Material:	Steel Comp E4340 Overall
Surface Treatment:	Chromate Overall And Cadmium Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30NF5-19> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.