

Description

Fastener Length: 2-5/64", Thread: 1/4-24, Thread Length: 29/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30NF523
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-581-6195
Schedule B:	7318.15.8085
ECCN:	9A991

NO IMAGE
AVAILABLE

P/N BACB30NF5-23 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.449 Inches Minimum And 0.459 Inches Maximum
Fastener Length:	2.033 Inches Minimum And 2.078 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.156 Inches Minimum And 0.171 Inches Maximum
Width Between Flats:	0.492 Inches Minimum And 0.502 Inches Maximum
Grip Diameter:	0.3104 Inches Minimum And 0.3120 Inches Maximum
Nominal Thread Diameter:	0.312 Inches
Grip Length:	1.428 Inches Minimum And 1.448 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	95000 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Part Name Assigned By Controlling Agency:	Bolt, Hex Head, 95 Ksi Shear, Short Thread, A286, Nonlocking
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Ams 5737 Assn Std Single Material Response Overall Or Ams 5853 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Amsqq-p-416, Ty 2, Cl 2 Plus Bps-f-69 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30NF5-23> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.