



Military-Fasteners.com

P/N BACB30NF5-45

Description

Fastener Length: 3-9/32", Thread: 1/4-24, Thread Length: 15/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30NF545
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-049-2998
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N BACB30NF5-45 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.429 Inches Minimum And 0.479 Inches Maximum
Fastener Length:	3.251 Inches Minimum And 3.281 Inches Maximum
Head Style:	Undercut Hexagon
Head Height:	0.156 Inches Minimum And 0.171 Inches Maximum
Width Between Flats:	0.492 Inches Minimum And 0.502 Inches Maximum
Grip Diameter:	0.3110 Inches Minimum And 0.3120 Inches Maximum
Nominal Thread Diameter:	0.312 Inches
Grip Length:	2.802 Inches Minimum And 2.822 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	140000 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	81205-bacb30nf Manufacturers Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30NF5-45> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.