

## P/N BACB30NN3K16

### **Description**

Fastener Length: 1-11/32", Thread: 10-32, Thread Length: 11/32

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: BACB30NN3K16

Minimum Qty (MOQ):

NSN: 5305-01-580-9571

Schedule B: 8108.90.3060

ECCN: EAR99

National Motor Freight: 096640, Screws, Iron Or Steel







<sup>\*</sup> See page 2 for technical characteristics

# P/N BACB30NN3K16 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.340 Inches Minimum And 0.350 Inches Maximum
Fastener Length:	1.330 Inches Minimum And 1.360 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.345 Inches Minimum And 0.383 Inches Maximum
Grip Diameter:	0.1881 Inches Minimum And 0.1895 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.990 Inches Minimum And 1.010 Inches Maximum
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Part Name Assigned By Controlling Agency:	Bolt,100 Deg,cross Recess,160ksi Min Tensile,long Thread
Material:	Titanium Alloy Overall
Surface Treatment:	Aluminum Overall
Thread Series Designator:	Unjf

## **How to Order**

Order this machine bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/BACB30NN3K16">https://military-fasteners.com/bolts/machine+bolts/BACB30NN3K16</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.