

Description

Fastener Length: 21/32", Thread: 10-32, Thread Length: 21/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30NN3K5
Minimum Qty (MOQ):	10
NSN:	5305-01-207-9349
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi

NO IMAGE
AVAILABLE

P/N BACB30NN3K5 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.320 Inches Minimum And 0.370 Inches Maximum
Fastener Length:	0.642 Inches Minimum And 0.672 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.345 Inches Minimum And 0.383 Inches Maximum
Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.302 Inches Minimum And 0.322 Inches Maximum
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Surface Finish:	63.0 Microinches Bearing Surface Of Head
Special Features:	Black Dye Or Paint On Thread End
Material:	Titanium Alloy Overall
Material Document And Classification:	Ams 4967 Assn Std Single Material Response Or Ams 4928 Assn Std Single Material Response Overall
Surface Treatment:	Aluminum Overall
Thread Series Designator:	Unjf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30NN3K5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.