

**Description**

Fastener Length: 1-59/64", Thread: 1/4-28, Thread Length: 27/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	BACB30NN4K24
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-580-9567
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	096640, Screws, Iron Or Steel

NO IMAGE  
AVAILABLE

## P/N BACB30NN4K24 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.420 Inches Minimum And 0.430 Inches Maximum
<b>Fastener Length:</b>	1.910 Inches Minimum And 1.940 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.465 Inches Minimum And 0.510 Inches Maximum
<b>Grip Diameter:</b>	0.2481 Inches Minimum And 0.2495 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Grip Length:</b>	1.490 Inches Minimum And 1.510 Inches Maximum
<b>Thread Quantity Per Inch:</b>	28
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Part Name Assigned By Controlling Agency:</b>	Bolt,100 Deg,cross Recess,160ksi Min Tensile,long Thread
<b>Material:</b>	Titanium Alloy Overall
<b>Surface Treatment:</b>	Aluminum Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30NN4K24> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.