

Description

Fastener Length: 2-11/64", Thread: 1/4-28, Thread Length: 27/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | BACB30NN4K28 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-01-580-9564 |
| Schedule B: | 8108.90.3060 |
| ECCN: | 9A991 |

NO IMAGE
AVAILABLE

P/N BACB30NN4K28 Specifications

| | |
|--------------------------------------------------|----------------------------------------------------------|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.420 Inches Minimum And 0.430 Inches Maximum |
| Fastener Length: | 2.160 Inches Minimum And 2.190 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.465 Inches Minimum And 0.510 Inches Maximum |
| Grip Diameter: | 0.2481 Inches Minimum And 0.2495 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 1.740 Inches Minimum And 1.760 Inches Maximum |
| Thread Quantity Per Inch: | 28 |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Part Name Assigned By Controlling Agency: | Bolt,100 Deg,cross Recess,160ksi Min Tensile,long Thread |
| Material: | Titanium Alloy Overall |
| Surface Treatment: | Aluminum Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30NN4K28> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.