

Description

Fastener Length: 39/64", Thread: 1/4-28, Thread Length: 27/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30NN4K3
Minimum Qty (MOQ):	10
NSN:	5305-01-580-9566
Schedule B:	8108.90.3060
ECCN:	EAR99



* See page 2 for technical characteristics

P/N BACB30NN4K3 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.420 Inches Minimum And 0.430 Inches Maximum
Fastener Length:	0.598 Inches Minimum And 0.628 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.465 Inches Minimum And 0.510 Inches Maximum
Grip Diameter:	0.2481 Inches Minimum And 0.2495 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.178 Inches Minimum And 0.198 Inches Maximum
Thread Quantity Per Inch:	28
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Part Name Assigned By Controlling Agency:	Bolt,100 Deg,cross Recess,160ksi Min Tensile,long Thread
Material:	Titanium Alloy Overall
Surface Treatment:	Aluminum Overall
Thread Series Designator:	Unjf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30NN4K3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.