

Description

Fastener Length: 1-1/16", Thread: 1/4-28, Thread Length: 25/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30NR4K11
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-338-6794
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N BACB30NR4K11 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.389 Inches Nominal
Fastener Length:	1.062 Inches Minimum And 1.092 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.678 Inches Minimum And 0.698 Inches Maximum
Thread Quantity Per Inch:	28
Surface Finish:	63.0 Microinches Bearing Surface Of Head32.0 Microinches Grip32.0 Microinches Threads
Special Features:	Aluminum Coating Identified By Red Dye On Thread End
Material:	Titanium Alloy Uns R56400 Overall
Material Document And Classification:	Ams4928 Assn Std Single Material Response Overall Or Ams4967 Assn Std Single Material Response Overall
Surface Treatment:	Aluminum Overall
Surface Treatment Document And Classification:	Bms 10-85 Ty1 National Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30NR4K11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.