

Description

Fastener Length: 2-9/16", Thread: 1/4-28, Thread Length: 25/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30NR4K33
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-580-6426
Schedule B:	8108.90.3060
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N BACB30NR4K33 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.384 Inches Minimum And 0.394 Inches Maximum
Fastener Length:	2.561 Inches Minimum And 2.606 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Grip Diameter:	0.248 Inches Minimum And 0.249 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	2.052 Inches Minimum And 2.072 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	95000 Pounds Per Square Inch
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Surface Finish:	63.0 Microinches Bearing Surface Of Head
Material:	Titanium Alloy Overall
Material Document And Classification:	Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall
Surface Treatment:	Aluminum Overall
Surface Treatment Document And Classification:	Bms10-85, Type 1, Class A Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30NR4K33> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.