

P/N BACB30NR4K36

Description

Fastener Length: 2-41/64", Thread: 1/4-28, Thread Length: 25/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	BACB30NR4K36
Minimum Qty (MOQ):	2
NSN:	5306-01-521-6049
Schedule B:	8108.90.3060
ECCN:	EAR99



^{*} See page 2 for technical characteristics

P/N BACB30NR4K36 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.389 Inches Nominal
Fastener Length:	2.639 Inches Nominal
Head Style:	Dished Hexagon
Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Grip Diameter:	0.2495 Inches Maximum
Single Shear Strength:	95000 Pounds Per Square Inch
End Item Identification:	Aircraft, B757
Nominal Thread Diameter:	0.250 Inches
Grip Length:	2.250 Inches Nominal
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Color:	Black Threads
Material:	Titanium Alloy Overall
Surface Treatment:	Aluminum Overall
Thread Series Designator:	Unjf

How to Order

Order this machine bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/BACB30NR4K36 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/BACB30NR4K36 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/machine+bolts/BACB30NR4K36 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/BACB30NR4K36 and selecting the quantity you want https://military-fasteners.com/bolts/BACB30NR4K36 and selecting the your cart you can check out https://military-fasteners.com/bolts/BACB30NR4K36 and selecting the your cart you can check out https://military-fasteners.com/bolts/BACB30NR4K36 are selecting the your cart your cart you can check you can