

Description

Fastener Length: 1-3/4", Thread: 1/4-24, Thread Length: 29/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | BACB30NR5K18 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5306-01-580-6445 |
| Schedule B: | 8108.90.3060 |
| ECCN: | EAR99 |

NO IMAGE
AVAILABLE

P/N BACB30NR5K18 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.449 Inches Minimum And 0.459 Inches Maximum |
| Fastener Length: | 1.720 Inches Minimum And 1.765 Inches Maximum |
| Head Style: | Dished Hexagon |
| Head Height: | 0.156 Inches Minimum And 0.171 Inches Maximum |
| Width Between Flats: | 0.492 Inches Minimum And 0.502 Inches Maximum |
| Grip Diameter: | 0.310 Inches Minimum And 0.312 Inches Maximum |
| Nominal Thread Diameter: | 0.312 Inches |
| Grip Length: | 1.115 Inches Minimum And 1.135 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 95000 Pounds Per Square Inch |
| Surface Finish: | 32.0 Microinches Grip |
| Surface Finish: | 32.0 Microinches Threads |
| Surface Finish: | 63.0 Microinches Bearing Surface Of Head |
| Material: | Titanium Alloy Overall |
| Material Document And Classification: | Ams 4928 Assn Std Single Material Response Overall Or Ams 4967 Assn Std Single Material Response Overall |
| Surface Treatment: | Aluminum Overall |
| Surface Treatment Document And Classification: | Bms10-85, Type 1, Class A Assn Std Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/BACB30NR5K18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.